

## **DECLARATION OF PERFORMANCE**

**N°: DoP-F**

**Rev. 5 – 22/09/2021**

1. Unique identification code of the product type:  
**DRY- PRESSED CERAMIC TILES, WITH WATER ABSORPTION  $E_b \leq 0,5\%$**
2. Intended uses:  
**FOR INTERNAL AND EXTERNAL WALLS AND FLOORINGS**
3. Name and contact address of the manufacturer:  
**EMILCERAMICA S.r.l. a socio unico**  
**Via GHIAROLA NUOVA, 29 41042 FIORANO M.SE (MO) ITALY**  
**Tel. : +39 0536 835111 Fax : +39 0536 835306**  
[contact@emilceramicagroup.it](mailto:contact@emilceramicagroup.it)    [www.emilgroup.it](http://www.emilgroup.it)
4. System of AVCP: **SYSTEM 4**
5. Name and identification number of notified laboratory: **NOT APPLICABLE**
6. Declared Performances:

| Declared Performance:                  |                            |          | EN 14411:2012                      |  |
|----------------------------------------|----------------------------|----------|------------------------------------|--|
| ESSENTIAL CHARACTERISTICS              | PERFORMANCE                |          | HARMONISED TECHNICAL SPECIFICATION |  |
| Reaction to fire                       | Class A1 <sub>fl</sub> /A1 |          | EN 14411:2012                      |  |
| Release for dangerous substances, for: | Cadmium                    | NPD      |                                    |  |
|                                        | Lead                       | NPD      |                                    |  |
| Breaking strength                      | Thickness ≥ 7,5 mm         | ≥ 1300 N |                                    |  |
|                                        | Thickness < 7,5 mm         | ≥ 700 N  |                                    |  |
| Slipperiness                           | See Annex 1/.....          |          |                                    |  |
| Tactility                              | NPD                        |          |                                    |  |
| Bond strength/adhesion                 | NPD                        |          |                                    |  |
| Thermal Shock Resistance               | Pass                       |          |                                    |  |
| Durability for:                        |                            |          |                                    |  |
| Internal Uses:                         | Pass                       |          |                                    |  |
| External Uses: freeze-thaw resistance  | Pass                       |          |                                    |  |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Fiorano M.se (MO)  
22/09/2021

Luca Gatti  
President



## **SLIPPERINNES: ANNEX 1 / VIVA**

Rev. 10 - 09/2021

|                  |                                | DIN<br>51130<br>(DE) | BCRA<br>D.M. 236/1989<br>(ITA) | UNE 41901:2017 EX (ESP) | CEN/TS 16165<br>Annex B                   |
|------------------|--------------------------------|----------------------|--------------------------------|-------------------------|-------------------------------------------|
| TEST METHOD USED |                                | Ramp                 | Tortus                         | Pendulum                | Ramp<br>(Critical angle $\alpha_{shod}$ ) |
| Series           | Surface                        | Value / class        |                                |                         |                                           |
| NR.21            | Naturale                       | R10                  | $\geq 0,40$                    | 2                       | $\geq 10$                                 |
| STATALE 9        | Naturale                       | R11                  | $\geq 0,40$                    | 2                       | $\geq 19$                                 |
| ACUSTICO 12      | Naturale                       | R10                  | $\geq 0,40$                    | 2                       | $\geq 10$                                 |
| 99 VOLTE         | Naturale                       | R10                  | $\geq 0,40$                    | NPD                     | $\geq 10$                                 |
| TERZO TEMPO      | Naturale                       | R10                  | $\geq 0,40$                    | NPD                     | $\geq 10$                                 |
|                  | Antislip                       | R11                  | $\geq 0,40$                    | NPD                     | $\geq 19$                                 |
| "+3"             | Naturale                       | R10                  | $\geq 0,40$                    | NPD                     | $\geq 10$                                 |
|                  | Antislip - 20 mm               | R11                  | $\geq 0,40$                    | 3                       | $\geq 19$                                 |
|                  | Lappato                        | NPD                  | NPD                            | NPD                     | NPD                                       |
| 300°             | Naturale                       | R10                  | $\geq 0,40$                    | 2                       | $\geq 10$                                 |
| L'H              | Naturale                       | R9                   | $\geq 0,40$                    | NPD                     | $\geq 6$                                  |
| NO CODE          | Laccato - Cerato               | R9                   | $\geq 0,40$                    | NPD                     | $\geq 6$                                  |
|                  | Tecnica                        | R11                  | $\geq 0,40$                    | 3                       | $\geq 19$                                 |
| DOTCOM           | Naturale                       | R10                  | $\geq 0,40$                    | 2                       | $\geq 10$                                 |
| YAKI             | Naturale                       | R9                   | $\geq 0,40$                    | NPD                     | $\geq 6$                                  |
| HERITAGE         | Naturale                       | R10                  | $\geq 0,40$                    | NPD                     | $\geq 10$                                 |
|                  | 20 mm                          | R11                  | $\geq 0,40$                    | 3                       | $\geq 19$                                 |
| NARCISO          | Naturale                       | R10                  | $\geq 0,40$                    | NPD                     | $\geq 10$                                 |
|                  | Full lappato -<br>Lappato matt | NPD                  | NPD                            | NPD                     | NPD                                       |
| METALLICA        | Naturale                       | R10                  | $\geq 0,40$                    | NPD                     | $\geq 10$                                 |
|                  | Slabs (120x278)                | R9                   | $\geq 0,40$                    | NPD                     | $\geq 6$                                  |
|                  | Metalbrick                     | NPD                  | NPD                            | NPD                     | NPD                                       |