

## **DECLARATION OF PERFORMANCE**

**N°: DoP-F**

**Rev. 5 – 22/09/2021**

1. Unique identification code of the product type:  
**DRY- PRESSED CERAMIC TILES, WITH WATER ABSORPTION  $E_b \leq 0,5\%$**
2. Intended uses:  
**FOR INTERNAL AND EXTERNAL WALLS AND FLOORINGS**
3. Name and contact address of the manufacturer:  
**EMILCERAMICA S.r.l. a socio unico**  
**Via GHIAROLA NUOVA, 29 41042 FIORANO M.SE (MO) ITALY**  
**Tel. : +39 0536 835111 Fax : +39 0536 835306**  
[contact@emilceramicagroup.it](mailto:contact@emilceramicagroup.it)    [www.emilgroup.it](http://www.emilgroup.it)
4. System of AVCP: **SYSTEM 4**
5. Name and identification number of notified laboratory: **NOT APPLICABLE**
6. Declared Performances:


ESSENTIAL CHARACTERISTICS	PERFORMANCE		HARMONISED TECHNICAL SPECIFICATION
<b>Reaction to fire</b>	Class A1 <sub>fl</sub> /A1		EN 14411:2012
<b>Release for dangerous substances, for:</b>	Cadmium	NPD	
	Lead	NPD	
<b>Breaking strength</b>	Thickness $\geq 7,5$ mm	$\geq 1300$ N	
	Thickness $< 7,5$ mm	$\geq 700$ N	
<b>Slipperiness</b>	See Annex 1/.....		
<b>Tactility</b>	NPD		
<b>Bond strength/adhesion</b>	NPD		
<b>Thermal Shock Resistance</b>	Pass		
<b>Durability for:</b>			
Internal Uses:	Pass		
External Uses: freeze-thaw resistance	Pass		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Fiorano M.se (MO)  
22/09/2021

Luca Gatti  
President



## SLIPPERINESS: ANNEX 1 / ERGON

Rev. 11 - 05-2022

		DIN 51130 (DE)	BCRA D.M. 236/1989 (ITA)	UNE 41901:2017 EX (ESP)	CEN/TS 16165 Annex B
TEST METHOD USED		Ramp	Tortus	Pendulum	Ramp (Critical angle $\alpha_{shod}$ )
Series	Surface	Value / class			
STONE PROJECT	Naturale	R10	≥ 0,40	NPD	≥ 10
	Lappato	R9	≥ 0,40	NPD	≥ 6
	Strutturato	R11	≥ 0,40	3	≥ 19
BACK 2 BACK	Naturale	R10	≥ 0,40	NPD	≥ 10
WOODTALK	Naturale	R11	≥ 0,40	2	≥ 19
	20mm	R11	≥ 0,40	3	≥ 19
ELEGANCE	Naturale	R10	≥ 0,40	NPD	≥ 10
	Lappato	NPD	NPD	NPD	NPD
	Bocciardato	R11	≥ 0,40	3	≥ 19
KYOTO	Naturale	R10	≥ 0,40	NPD	≥ 10
ARCHITECT RESIN	Naturale	R10	NPD	2	≥ 10
	Lappato	NPD	NPD	NPD	NPD
LIMESTONE	Naturale	R10	≥ 0,40	2	≥ 10
	Lappato	R9	≥ 0,40	NPD	≥ 6
	Antislip	R11	≥ 0,40	NPD	≥ 19
PLAYGROUND	Naturale	R10	≥ 0,40	2	≥ 10
	Lappato	NPD	NPD	NPD	NPD
METAL STYLE	Naturale	R10	≥ 0,40	NPD	≥ 10
METAL.IT	Naturale	R10	≥ 0,40	NPD	≥ 10
	Lappato	NPD	NPD	NPD	NPD
TR3ND	Naturale	R10	≥ 0,40	1	≥ 10
	Majolica	NPD	NPD	NPD	NPD
CORNERSTONE	Naturale	R10	≥ 0,40	2	≥ 10
	20mm	R11	≥ 0,40	3	≥ 19
STONE TALK	Naturale	R10	≥ 0,40	NPD	≥ 10
	Lappato	NPD	NPD	NPD	NPD
	Tecnica - 20 mm	R11	≥ 0,40	3	≥ 19
GRAINSTONE	Naturale	R10	≥ 0,40	NPD	≥ 10
	Tecnica - 20 mm	R11	≥ 0,40	3	≥ 19
	Lappato	NPD	NPD	NPD	NPD
LOMBARDA	Naturale	R10	≥ 0,40	NPD	≥ 10
	Tecnica - 20 mm	R11	≥ 0,40	3	≥ 19
	Lappato	NPD	NPD	NPD	NPD
WOODTOUCH	Natural	R10	≥ 0,40	2	≥ 10
	Tecnica - 20 mm	R11	≥ 0,40	3	≥ 19
	Soft	R9	≥ 0,40	NPD	≥ 6
MEDLEY	Naturale	R10	≥ 0,40	NPD	≥ 10
	Tecnica - 20 mm	R11	≥ 0,40	3	≥ 19
CORNERSTONE ALPEN	Naturale	R10	≥ 0,40	NPD	≥ 10
	20 mm	R11	≥ 0,40	3	≥ 19
ELEGANCE PRO	Naturale	R10	≥ 0,40	NPD	≥ 10
	Bocciardato - 20 mm	R11	≥ 0,40	3	≥ 19
	Lappato	NPD	NPD	NPD	NPD
CORNERSTONE (slim)	Naturale	R10	≥ 0,40	2	≥ 10
OROS STONE	Naturale	R10	≥ 0,40	NPD	≥ 10
	Tecnica - 20 mm	R11	≥ 0,40	3	≥ 19
ABACUS	Lux	NPD	NPD	NPD	NPD
	Matt	NPD	NPD	NPD	NPD